

## RSK 7152412



The F92 S floor drain has a 75mm side outlet and is for installation in wooden or concrete joists. It comes complete with a removable stainless steel NOOD water trap, clamping ring and plastic grate. The NOOD water trap is a mechanical trap which closes when there is no water present, thus preventing any foul air from escaping through the drain. It also acts as a 1m water column and prevents backflow. The floor drain also comes with a protective cover that is intended to prevent any concrete or debris from installation from entering the drain.

The automatic clamping ring is used for both sealing membrane and vinyl flooring. It is a self-adjusting clamping ring for vinyl flooring with a thickness of 1,5 mm to 2 mm.

### Specifications

|                           |   |
|---------------------------|---|
| <b>RSK Number</b>         | 7152412                                   |
| <b>Floor Covering</b>     | Concrete/Resin/Tiles/Vinyl                |
| <b>Function</b>           | Side outlet                               |
| <b>Item Color</b>         | Stainless                                 |
| <b>Material</b>           | Acid-resistant stainless steel 1.4404, PP |
| <b>Outlet Dimension</b>   | Ø75 mm                                    |
| <b>Pressure Flow Temp</b> | 1,0 l/s                                   |

|                |                      |
|----------------|----------------------|
| <b>Size</b>    | Ø150 mm              |
| <b>Surface</b> | Cold rolled (2B)     |
| <b>Version</b> | With NOOD water trap |

