



RSK 7099506

Outlet gully untrapped in acid-resistant stainless steel with Ø75 side outlet and Ø110 connection to the drainage channel.

RSK 7099506

Outlet gully untrapped in acid-resistant stainless steel with Ø75 side outlet and Ø150 connection to the drainage channel.

RSK 7099517

Outlet gully untrapped in acid-resistant stainless steel with Ø75 side outlet and Ø220 connection to the drainage channel.

RSK 7099514

Outlet gully untrapped in acid-resistant stainless steel with Ø75 vertical outlet and Ø150 connection to the drainage channel.

Specifications

RSK Number	7099506
Construction Height	125
Flow	3,6
Function	Side outlet
Item Color	Stainless

Material	Acid-resistant stainless steel 1.4404
Outlet Dimension	Ø75 mm
Pressure Flow Temp	3,6 l/s
Size	110
Surface	Cold rolled (2B)
Version	Untrapped

Item Number	HA305405PR
Construction Height	196
Flow	>5,2
Function	Side outlet
Item Color	Stainless

Material	Acid-resistant stainless steel 1.4404
Outlet Dimension	Ø75 mm
Size	150
Surface	Cold rolled (2B)
Version	Untrapped

RSK Number	7099517
Construction Height	171

Flow	>5,2
Function	Side outlet
Item Color	Stainless
Material	Acid-resistant stainless steel 1.4404
Outlet Dimension	Ø75 mm
Pressure Flow Temp	5,2 l/s
Size	220
Surface	Cold rolled (2B)
Version	Untrapped
RSK Number	7099514
Construction Height	137
Flow	>5,2
Function	Side outlet
Item Color	Stainless
Material	Acid-resistant stainless steel 1.4404
Outlet Dimension	Ø75 mm
Pressure Flow Temp	5,2 l/s
Size	150
Surface	Cold rolled (2B)

Version

Untrapped

