

## RSK 7098854



Purus channel 100 modul 50-65 is a floor channel made of acid-resistant stainless steel for installation in concrete. The floor channel is intended for concrete, epoxy and tile floors without a waterproofing membrane. The floor channel is 100 mm wide and has a built-in fall of which the height is 50 mm and 65 mm and a length of 2500 mm. The floor channel is delivered with gasket and screw connection for installation but needs to be supplemented with grid depending on the environment and outlet house. The total height with screw joints is 129 mm.

## RSK 7098855

Purus channel 100 modul 65-80 is a floor channel made of acid-resistant stainless steel for installation in concrete. The floor channel is intended for concrete, epoxy and tile floors without a waterproofing membrane. The floor channel is 100 mm wide and has a built-in fall of which the height is 65 mm and 80 mm and a length of 2500 mm. The floor channel is delivered with gasket and screw connection for installation but needs to be supplemented with grid depending on the environment and outlet house. The total height with screw joints is 129 mm.

## RSK 7098856

Purus channel 100 modul 80-95 is a floor channel made of acid-resistant stainless steel for installation in concrete. The floor channel is intended for concrete, epoxy and tile floors without a waterproofing

membrane. The floor channel is 100 mm wide and has a built-in fall of which the height is 80 mm and 95 mm and a length of 2500 mm. The floor channel is delivered with gasket and screw connection for installation but needs to be supplemented with grid depending on the environment and outlet house. The total height with screw joints is 129 mm.

RSK 7098857

Purus channel 100 modul 95-110 is a floor channel made of acid-resistant stainless steel for installation in concrete. The floor channel is intended for concrete, epoxy and tile floors without a waterproofing membrane. The floor channel is 100 mm wide and has a built-in fall of which the height is 95 mm and 110 mm and a length of 2500 mm. The floor channel is delivered with gasket and screw connection for installation but needs to be supplemented with grid depending on the environment and outlet house. The total height with screw joints is 129 mm.

## Specifications

<b>RSK Number</b>	7098854
<b>Floor Construction</b>	Concrete flooring
<b>Floor Covering</b>	Concrete
<b>Function</b>	With slope
<b>Item Color</b>	Stainless
<b>Material</b>	Acid-resistant stainless steel 1.4404

<b>Size</b>	2500×100 mm
<b>Surface</b>	Pickled
<b>Version</b>	Do not forget grid/grating
<b>RSK Number</b>	7098855
<b>Floor Construction</b>	Concrete flooring
<b>Floor Covering</b>	Concrete
<b>Function</b>	With slope
<b>Item Color</b>	Stainless
<b>Material</b>	Acid-resistant stainless steel 1.4404
<b>Size</b>	2500×100 mm
<b>Surface</b>	Pickled
<b>Version</b>	Do not forget grid/grating
<b>RSK Number</b>	7098856
<b>Floor Construction</b>	Concrete flooring
<b>Floor Covering</b>	Concrete
<b>Function</b>	With slope
<b>Item Color</b>	Stainless
<b>Material</b>	Acid-resistant stainless steel 1.4404
<b>Size</b>	2500×100 mm

<b>Surface</b>	Pickled
<b>Version</b>	Do not forget grid/grating
<b>RSK Number</b>	7098857
<b>Floor Construction</b>	Concrete flooring
<b>Floor Covering</b>	Concrete
<b>Function</b>	With slope
<b>Item Color</b>	Stainless
<b>Material</b>	Acid-resistant stainless steel 1.4404
<b>Size</b>	2500×100 mm
<b>Surface</b>	Pickled
<b>Version</b>	Do not forget grid/grating

