

RSK 7098766



Purus channel combo is made of acid-resistant stainless steel with side outlet Ø75 mm for installation in concrete. The floor channel is 300x300x150 och är avsedd för massagolv som ytskick. There is always residual water in the channel about 50 mm of water forms the water trap in the bottom of the channel and is equipped with a cleaning plug. The floor channel requires an almost continuous flow to function properly. Unsuitable in environments that set hygiene requirements.

RSK 7098768

Purus channel combo is made of acid-resistant stainless steel with side outlet Ø75 mm for installation in concrete. The floor channel is 500x300x150 och är avsedd för massagolv som ytskick. There is always residual water in the channel about 50 mm of water forms the water trap in the bottom of the channel and is equipped with a cleaning plug. The floor channel requires an almost continuous flow to function properly. Unsuitable in environments that set hygiene requirements.

Specifications

RSK Number	7098766
Construction Height	150
Floor Construction	Concrete flooring

Floor Covering	Resin
Flow	1,3
Function	Side outlet
Item Color	Stainless
Material	Acid-resistant stainless steel 1.4404
Outlet Dimension	Ø75 mm
Pressure Flow Temp	1,3 l/s
Size	300x300x150 mm
Surface	Pickled
Version	Do not forget grid/grating
RSK Number	7098768
Construction Height	150
Floor Construction	Concrete flooring
Floor Covering	Resin
Flow	1,3
Function	Side outlet
Item Color	Stainless
Material	Acid-resistant stainless steel 1.4404
Outlet Dimension	Ø75 mm

**Pressure Flow
Temp**

1,3 l/s

Size

500x300x150 mm

Surface

Pickled

Version

Do not forget grid/grating

Dimension (mm)	LxWxH (mm)	Ø (mm)
300x300x150	303 x 303 x 150	75
300x300x200	303 x 303 x 200	110
500x300x150	503 x 303 x 150	75
500x300x200	503 x 303 x 200	110

