

RSK 7098740



Purus channel spalte module 60-75 is a floor channel made of acid-resistant stainless steel for installation in concrete. The floor channel is intended for concrete, epoxy and tile floors without a waterproofing membrane. Purus channel spalte module is only 20 mm wide, has a built-in fall of which the height is 60 mm and 75 mm and a length of 2500 mm. Purus channel spalte module is delivered with gasket and screw connection for installation but needs to be supplemented with grid depending on the environment and outlet house. The total height with screw joints is 124 mm.

RSK 7098741

Purus channel spalte module 75-90 is a floor channel made of acid-resistant stainless steel for installation in concrete. The floor channel is intended for concrete, epoxy and tile floors without a waterproofing membrane. Purus channel spalte module is only 20 mm wide, has a built-in fall of which the height is 75 mm and 90 mm and a length of 2500 mm. Purus channel spalte module is delivered with gasket and screw connection for installation but needs to be supplemented with grid depending on the environment and outlet house. The total height with screw joints is 124 mm.

RSK 7098742

Purus channel spalte module 95-105 is a floor channel made of acid-resistant stainless steel for installation in concrete. The floor channel is intended for concrete, epoxy and tile floors without a

waterproofing membrane. Purus channel spalte module is only 20 mm wide, has a built-in fall of which the height is 95 mm and 105 mm and a length of 2500 mm. Purus channel spalte module is delivered with gasket and screw connection for installation but needs to be supplemented with grid depending on the environment and outlet house. The total height with screw joints is 124 mm.

RSK 7098743

Purus channel spalte module 105-120 is a floor channel made of acid-resistant stainless steel for installation in concrete. The floor channel is intended for concrete, epoxy and tile floors without a waterproofing membrane. Purus channel spalte module is only 20 mm wide, has a built-in fall of which the height is 105 mm and 120 mm and a length of 2500 mm. Purus channel spalte module is delivered with gasket and screw connection for installation but needs to be supplemented with grid depending on the environment and outlet house. The total height with screw joints is 124 mm.

Specifications

RSK Number	7098740
Floor Construction	Concrete flooring
Floor Covering	Concrete/Resin/Tiles
Item Color	Stainless
Material	Acid-resistant stainless steel 1.4404

Size	2500×20 mm
Surface	Pickled
Version	20 mm gap, without grate
RSK Number	7098741
Floor Construction	Concrete flooring
Floor Covering	Concrete/Resin/Tiles
Item Color	Stainless
Material	Acid-resistant stainless steel 1.4404
Size	2500×20 mm
Surface	Pickled
Version	20 mm gap, without grate
RSK Number	7098742
Floor Construction	Concrete flooring
Floor Covering	Concrete/Resin/Tiles
Item Color	Stainless
Material	Acid-resistant stainless steel 1.4404
Size	2500×20 mm
Surface	Pickled
Version	20 mm gap, without grate

RSK Number	7098743
Floor Construction	Concrete flooring
Floor Covering	Concrete/Resin/Tiles
Item Color	Stainless
Material	Acid-resistant stainless steel 1.4404
Size	2500×20 mm
Surface	Pickled
Version	20 mm gap, without grate

D1	D2	L (mm)
120	105	1000
105	90	1000
90	75	1000
75	60	1000
120	105	2500
105	90	2500
90	75	2500
75	60	2500

