

## RSK 7114617



The Purus Line 600 is a super low-level linear floor drain body with a height of just 59mm and a horizontal 50 mm outlet. It is designed for installation in concrete joists. The Purus Line comes with a removable NOOD water trap, strainer, stainless steel clamping ring, stainless steel frame and installation kit. It is compatible with the 600 Patterned and Limited Edition grates, which are sold separately. The NOOD water trap is a mechanical trap which closes when there is no water present, thus preventing any foul air from escaping through the drain. This linear floor drain can be installed against the wall or elsewhere in the room. For wooden joists with poured concrete, you should use the side or gable outlet versions instead.

## RSK 7114622

The Purus Line 700 is a super low-level linear floor drain body with a height of just 59mm and a horizontal 50 mm outlet. It is designed for installation in concrete joists. The Purus Line comes with a removable NOOD water trap, strainer, stainless steel clamping ring, stainless steel frame and installation kit. It is compatible with the 700 Patterned and Limited Edition grates, which are sold separately. The NOOD water trap is a mechanical trap which closes when there is no water present, thus preventing any foul air from escaping through the drain. This linear floor drain can be installed against the wall or elsewhere in the room. For wooden joists with poured concrete, you should use the side or gable outlet versions instead.

## RSK 7114627

The Purus Line 800 is a super low-level linear floor drain body with a height of just 59mm and a horizontal 50 mm outlet. It is designed for installation in concrete joists. The Purus Line comes with a removable NOOD water trap, strainer, stainless steel clamping ring, stainless steel frame and installation kit. It is compatible with the 800 Patterned and Limited Edition grates, which are sold separately. The NOOD water trap is a mechanical trap which closes when there is no water present, thus preventing any foul air from escaping through the drain. This linear floor drain can be installed against the wall or elsewhere in the room. For wooden joists with poured concrete, you should use the side or gable outlet versions instead.

## RSK 7114632

The Purus Line 900 is a super low-level linear floor drain body with a height of just 59mm and a horizontal 50 mm outlet. It is designed for installation in concrete joists. The Purus Line comes with a removable NOOD water trap, strainer, stainless steel clamping ring, stainless steel frame and installation kit. It is compatible with the 900 Patterned and Limited Edition grates, which are sold separately. The NOOD water trap is a mechanical trap which closes when there is no water present, thus preventing any foul air from escaping through the drain. This linear floor drain can be installed against the wall or elsewhere in the room. For wooden joists with poured concrete, you should use the side or gable outlet versions instead.

## RSK 7114637

The Purus Line 1000 is a super low-level linear floor drain body with a height of just 59mm and a horizontal 50 mm outlet. It is designed for installation in concrete joists. The Purus Line comes with a removable NOOD water trap, strainer, stainless steel clamping ring, stainless steel frame and installation kit. It is compatible with the 1000 Patterned and Limited Edition grates, which are sold separately. The NOOD water trap is a mechanical trap which closes when there is no water present, thus preventing any foul air from escaping through the drain. This linear floor drain can be installed against the wall or elsewhere in the room. For wooden joists with poured concrete, you should use the side or gable outlet versions instead.

**RSK 7114675**

The Purus Line 1200 is a super low-level linear floor drain body with a height of just 59mm and a horizontal 50 mm outlet. It is designed for installation in concrete joists. The Purus Line comes with a removable NOOD water trap, strainer, stainless steel clamping ring, stainless steel frame and installation kit. It is compatible with the 1200 Patterned and Limited Edition grates, which are sold separately. The NOOD water trap is a mechanical trap which closes when there is no water present, thus preventing any foul air from escaping through the drain. This linear floor drain can be installed against the wall or elsewhere in the room. For wooden joists with poured concrete, you should use the side or gable outlet versions instead.

## Specifications

**RSK Number**

7114617

<b>Floor Construction</b>	Concrete flooring
<b>Floor Covering</b>	Tiles
<b>Function</b>	Side outlet, low-rise
<b>Item Color</b>	Grey
<b>Material</b>	ABS, PP, Stainless steel 1.4301
<b>Outlet Dimension</b>	Ø50 mm
<b>Pressure Flow Temp</b>	0,6 l/s
<b>Size</b>	600
<b>Version</b>	With frame and no grating

<b>RSK Number</b>	7114622
<b>Floor Construction</b>	Concrete flooring
<b>Floor Covering</b>	Tiles
<b>Function</b>	Side outlet, low-rise
<b>Item Color</b>	Grey
<b>Material</b>	ABS, PP, Stainless steel 1.4301
<b>Outlet Dimension</b>	Ø50 mm
<b>Pressure Flow Temp</b>	0,6 l/s
<b>Size</b>	700

<b>Version</b>	With frame and no grating
<b>RSK Number</b>	7114627
<b>Floor Construction</b>	Concrete flooring
<b>Floor Covering</b>	Tiles
<b>Function</b>	Side outlet, low-rise
<b>Item Color</b>	Grey
<b>Material</b>	ABS, PP, Stainless steel 1.4301
<b>Outlet Dimension</b>	Ø50 mm
<b>Pressure Flow Temp</b>	0,6 l/s
<b>Size</b>	800
<b>Version</b>	With frame and no grating
<b>RSK Number</b>	7114632
<b>Floor Construction</b>	Concrete flooring
<b>Floor Covering</b>	Tiles
<b>Function</b>	Side outlet, low-rise
<b>Item Color</b>	Grey
<b>Material</b>	ABS, PP, Stainless steel 1.4301
<b>Outlet Dimension</b>	Ø50 mm

<b>Pressure Flow Temp</b>	0,6 l/s
<b>Size</b>	900
<b>Version</b>	With frame and no grating
<b>RSK Number</b>	7114637
<b>Floor Construction</b>	Concrete flooring
<b>Floor Covering</b>	Tiles
<b>Function</b>	Side outlet, low-rise
<b>Item Color</b>	Grey
<b>Material</b>	ABS, PP, Stainless steel 1.4301
<b>Outlet Dimension</b>	Ø50 mm
<b>Pressure Flow Temp</b>	0,6 l/s
<b>Size</b>	1000
<b>Version</b>	With frame and no grating
<b>RSK Number</b>	7114675
<b>Floor Construction</b>	Concrete flooring
<b>Floor Covering</b>	Tiles
<b>Function</b>	Side outlet, low-rise
<b>Item Color</b>	Grey

**Material** ABS, PP, Stainless steel 1.4301

**Outlet Dimension** Ø50 mm

**Pressure Flow  
Temp** 0,6 l/s

**Size** 1200

**Version** With frame and no grating

